

# Industrial HP35

## GLASS-PTFE

HPP Performance HPPSTIK Industrial HP35 is fiberglass fabric impregnated with PTFE (polytetrafluoroethylene) dispersion and coated with high-temperature, pressure-sensitive silicone adhesive.

Hi-Performance Products, Inc.  
1231 Puerta Del Sol; Unit 400  
San Clemente CA 92673  
Customer Service: (949) 366-6088  
FAX: (949) 366-5988

### Typical Properties

Product Number	HP35-03	HP35-05	HP35-06	HP35-10
Backing Material	PTFE-Coated Fiberglass Fabric	PTFE-Coated Fiberglass Fabric	PTFE-Coated Fiberglass Fabric	PTFE-Coated Fiberglass Fabric
Adhesive Type	Super Stick Silicone	Super Stick Silicone	Super Stick Silicone	Super Stick Silicone
Total Thickness (in.)	.0053	.0073	.0083	.0105
Backing Thickness (in.)	.0030	.0050	.0060	.0080
Adhesive Thickness (in.)	.0023	.0023	.0023	.0025
Adhesion to Steel (oz./in.)	50	60	65	80
Elongation (% at break)	<5	<5	<5	<5
Operating Temperature (°F)	-100 to 500	-100 to 500	-100 to 500	-100 to 500
Color	Natural	Natural	Natural	Natural

[www.ptfeglass.com](http://www.ptfeglass.com)

Limited Warranty: For a period of 6 months from the date of first sale, Hi-Performance Products, Inc. warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s). Hi-Performance Products, Inc. DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Values shown are typical. Certified test reports for writing specifications are available.

#### Applications—HPP Performance

Industrial HP35 is frequently used by the packaging industry as a release surface on heat sealers, blister formation and form-fill-seal equipment. The durability and anti-stick properties of HP35 also make it an ideal material for the lining of guide rails, chutes and slides. The high temperature capabilities and non-stick properties of HP35 allow it to perform as an excellent release surface in the composite aircraft industry.

Features/Benefits—HP35 is a very durable and versatile product. The combination of PTFE, fiberglass and a high-temperature silicone adhesive allows HP35 to perform in continuous

temperatures up to 500°F. HP35 is dimensionally stable and resistant to tears, punctures, abrasion and wear. It will not "cold flow" under heavy loads.

Availability—HP35 is available in 3, 5, 6 and 10 mil thicknesses and widths from 1/4" to 39" wide. Standard roll length is 18 or 36 yards long. HP35 is available with or without a liner.

NOTE: Hi-Performance Products, Inc. does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s) or of any final product into which the product(s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.